



PRODUCT CODE: HS-HAR2-POINT **PRODUCT DESCRIPTION:** Basic 2 point harness, no lanyard

PRODUCT COMPLIANCE

CERTIFICATION	EN361:2002 – Polyester full body harness
PACKAGING	Individually packed in a box and serial numbered, with user instruction leaflet

MATERIALS

WEBBING	<ul style="list-style-type: none"> • 45mm wide Polyester webbing • Multi-colour webbing to indicate correct positioning prior to donning
----------------	--

TECHNICAL FEATURES

HARNESS	<ul style="list-style-type: none"> • Full body harness, with adjustable leg straps • Sternal D-ring for means of connection at the chest, as well as back mounted D-ring for connection at the back • Padded foam back support for superior comfort • Lanyard with scaffold hooks can be purchased separately
PARKING POINTS	Plastic parking point buckle, fitted on webbing loop. Removes tripping hazard, but breaks between 25-50kg as safety precaution. Can be purchased separately (HS-HARFABUC).

WARNINGS

MAXIMUM WEIGHT	Maximum permissible user weight is 100kg.
FALL FACTOR	Total length of harness is 3.5m (1.75m lanyard + 1.75m absorber) when fully deployed (lanyard must be purchased separately). We recommend connecting to an anchor point that is above the user where possible (as opposed to waist height or below), in order to limit the amount of free fall that would occur if the user fell.
FALL PROTECTION	This is a basic harness only. Please ensure that you have consulted with a fall arrest expert to assess all fall risks in your working environment. Your REBEL representative can recommend an expert if required.
PRODUCT LIFESPAN	This product MUST be removed from service 5 years after its manufacturing date.

SUGGESTED ENVIRONMENTS

Basic fall arrest only. **NB! Not to be used for work positioning, rope access or rescue.**