



PRODUCT CODE: HS-DBLLAN

PRODUCT DESCRIPTION: Detachable shock absorbing double lanyard with scaffold hooks

PRODUCT COMPLIANCE

CERTIFICATION	EN354:2010 – Polyester lanyard EN355:2002 – Polyester energy absorber protected by thermoplastic sheath EN362:2004 – connecting devices
PACKAGING	Individually packed in a box and serial numbered, with user instruction leaflet

MATERIALS

WEBBING	<ul style="list-style-type: none"> • 30mm wide Polyester webbing • Bright coloured webbing to make it easier to differentiate the lanyard from the harness
SCAFFOLD HOOKS	55mm opening steel hook with automatic locking gate device and safety catch

TECHNICAL FEATURES

LANYARD	1.75 m double lanyard attached to shock absorber
SCAFFOLD HOOKS	Large opening hook for easy connections to larger anchorage points
SHOCK ABSORBER	Does not allow forces over 6kN on the user
CARABINER	Screw gate carabiner with automatic closing function. Connects the lanyard to the harness.
BLACK LINING	Double reinforced to reduce wear and tear at tension points

WARNINGS

MAXIMUM WEIGHT	Certified to a maximum of 100kg. If user is over 100kg, with a maximum of 120kg, they MUST be connected above their shoulders to an anchor point which is designed to withstand a minimum of 15kN.
FALL FACTOR	Total length of lanyard is 3.5m (1.75m lanyard + 1.75m absorber) when fully deployed. We recommend connecting to an anchor point that is above the user where possible (as opposed to waist height or below), in order to limit the amount of free fall that would occur if the user fell.
FALL PROTECTION	This is a basic lanyard only. Please ensure that you have consulted with a fall arrest expert to assess all fall risks in your working environment. Your REBEL representative can recommend an expert if required.
PRODUCT LIFESPAN	This product MUST be removed from service 5 years after its manufacturing date.

SUGGESTED ENVIRONMENTS

Basic fall arrest only. **NB! Not to be used for work positioning, rope access or rescue.**