

PRODUCT SPECIFICATIONS RE811-S3 S3 CHUKKA BOOT The iconic work boot



PRODUCT CODE: RE811-S3

PRODUCT NAME: S3 CHUKKA BOOT

PRODUCT DESCRIPTION: The iconic work boot

INFORMATION

COLOURBlackSIZE RANGE3-13 (unisex, starts from a size 3)ISO 20345 CLASSIFICATIONS3- anti-static, energy absorption of seat region, anti-penetration and water resistantSLIP RESISTANCE CLASSIFICATION SRA / SRB / SSC- tested for slip resistance in environments of ceraming and water resistantsCONSTRUCTIONInjection moulded construction processSABSSABS approved and mark bearingNRCS APPROVAL NONRCS/9002/2020/051		
ISO 20345 CLASSIFICATION S3 - anti-static, energy absorption of seat region, anti-penetration and water resistant SLIP RESISTANCE CLASSIFICATION SRA / SRB / SRC SRC - tested for slip resistance in environments of ceramic and metal surfaces with soapy and oily solutions CONSTRUCTION Injection moulded construction process SABS SABS approved and mark bearing	COLOUR	Black
SLIP RESISTANCE CLASSIFICATION SRA / SRB / SRC SRC - tested for slip resistance in environments of ceramic and metal surfaces with soapy and oily solutions CONSTRUCTION Injection moulded construction process SABS SABS approved and mark bearing	SIZE RANGE	3 – 13 (unisex, starts from a size 3)
SLIP RESISTANCE CLASSIFICATION SRA / SRB / SRC with soapy and oily solutions CONSTRUCTION Injection moulded construction process SABS SABS approved and mark bearing	ISO 20345 CLASSIFICATION	S3 – anti-static, energy absorption of seat region, anti-penetration and water resistant
SABS SABS approved and mark bearing	SLIP RESISTANCE CLASSIFICATION SRA / SRB / SRC	
	CONSTRUCTION	Injection moulded construction process
NRCS APPROVAL NO NRCS/9002/262020/0051	SABS	SABS approved and mark bearing
	NRCS APPROVAL NO	NRCS/9002/262020/0051

MATERIALS UPPER High quality barton print full grain leather complete with S2 water resistant coating Dual density polyurethane (PU) SOLE **EYELETS** Nickel-free D-rings Black taibrelle mesh and microfiber LINING TOE CAP 200J steel toe cap FOOTBED (INSOLE) Moulded polyurethane (PU); taibrelle mesh upper with contoured heel and arch **INSOLE BOARD** 3MR Ibitech non-woven insole board

SPECIAL FEATURES • Water resistant coating UPPER Hi-viz reflective safety strip for added visibility

MIDSOLE	Steel midsole for anti-penetration protection
OTHER	Thermoplastic polyurethane (TPU) toe bumper for added scuff protection

KEY FEATURES



SUGGESTED ENVIRONMENTS

Agriculture, construction, electricians, engineering, fishing and allied industries, general applications, mining, motor industry, chemical and petrochemical, production lines, refineries, transport.

